

DS-KIS606-P Network Video Intercom Kit



- Network video intercom kit for villa
- One-press call button for easier calls
- Convenient Hik-Connect APP mobile control
- Device included: DS-KV6113-PE1(C) × 1, DS-KH6110-WE1 × 1, DS-KABV6113-RS × 1, PSU × 2
- Power adapter included in the package

▪ Specification

Door station	
System parameters	
Operation system	Linux
Processor	Embedded high performance processor
RAM	256 MB
ROM	32 MB
Video parameters	
Supplement light	IR light, up to 3 m
Resolution	Main stream: 1920 × 1080p Sub stream: 704 × 576p
Lens	2MP HD camera
Wide dynamic range (WDR)	120 dB
Field of view	Horizontal: 131°, Vertical: 78°
Video Compression Standard	H.264
Audio parameters	
Audio input	1 built-in omnidirectional microphone
Audio output	1 built-in loudspeaker
Audio quality	Noise suppression and echo cancellation
Volume adjustment	Adjustable
Audio compression standard	G.711 U
Audio compression Rate	64 Kbps
Capacity parameters	
User capacity	2000
Linked indoor station capacity	16
Card capacity	10000
Protocol	
Network protocol	TCP/IP, RSTP
Device interfaces	
RS-485	1
Network interface	1 RJ-45, 10/100 Mbps self-adaptive
Alarm input	4
Lock control	1 relay, Max. 30 VDC 2 A
Exit button	1
Door contact input	1
TAMPER	1
General	
Button	1 physical button
Power consumption	< 10 W
Working temperature	-40 °C to 55 °C(-40 °F to 131 °F)
Working humidity	10% to 95% (no-condensing)
Dimension	138 mm × 65 mm × 27 mm (5.4" × 2.6" × 1.1")
Installation	Surface mounting

Protection level	IP65
Indicator	2
Power supply	IEEE802.3af, standard PoE 12 VDC
Application environment	Outdoor
Weight	Net weight: 0.190 kg ; Gross weight: 0.414 kg
Indoor station	
System parameters	
Operation system	Embedded Linux operation system
RAM	128 MB
ROM	16 MB
Processor	Embedded processor
Display parameters	
Display resolution	480 × 272
Operation method	Capacitive touch screen with 9 touch buttons
Screen size	4.3-inch colorful TFT screen
Type	Colorful TFT screen
Video parameters	
Video compression standard	/
Resolution	/
Lens	/
Wide dynamic range (WDR)	/
FOV	/
Audio parameters	
Audio input	Built-in omnidirectional microphone
Audio output	Built-in loudspeaker
Audio quality	Noise suppression and echo cancellation
Audio compression standard	G.711 U, G.711 A
Volume adjustment	Adjustable
Audio compression bitrate	64 Kps
Capacity parameters	
Notice capacity	200
Linked indoor extensions capacity	16
Indoor station	
Wi-Fi	Wi-Fi 802.11 b/g/n, 2.4 GHz
Network protocol	TCP/IP, SIP, RTSP
Device interfaces	
Network interface	1 RJ-45 10/100 Mbps self-adaptive
General	
Power consumption	≤ 4 W
Button	9 physical button
Power supply	IEEE802.3af, Standard PoE, 12 VDC
Working temperature	-10 °C to 50 °C (14 °F to 122 °F)
Working humidity	10% to 95% (no-condensing)

Dimension (L x W x H)	200 mm × 140 mm × 15.1 mm (7.9" × 5.5" × 0.6")
Dimension (W × H × D)	120 mm × 120 mm × 21 mm (4.7" × 4.7" × 0.83")
Installation	Wall mounting, table mounting
Application environment	Indoor
Protective level	/
Weight	With package: 336.6 g Without package: 197.8 g
Language	English, French, Portuguese, Portuguese (Brazil), Spanish, Russian, German, Italian, Polish, Turkish, Vietnamese, Arabic, Czech, Hungarian, Dutch, Romanian, Bulgarian, Ukrainian, Croatian, Serbian, Greek, Lithuanian, Estonian, Latvian, Norwegian Danish, Slovenian, Slovak, Swedish, Finnish, Traditional Chinese, Mongolian, Hebrew, Kazakh, Uzbek

▪ **Available Model**

DS-KIS606-P

▪ **Accessory**

▪ **Included**

DS-KABV6113-RS

Villa Door Station

Rain Shield



▪ **Optional**

DS-KABH6350-T



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

